

EXISS

THE MARK OF EXCELLENCE

ALL-ALUMINUM LIVESTOCK TRAILERS



A BETTER TRAILER

Rugged, durable and dependable Exiss[®] Livestock Trailers have been the choice of cattlemen for years. With its aluminum construction and its great reputation for value, it's easy to see why. Since 1994, Exiss has built trailers that set the standard for quality, dependability and value. Today, our standards are still the same. We build trailers that last, making hauling your livestock year after year.



**GUARANTEED EXCELLENCE
IS OUR COMMITMENT**

Exiss is a proud member of the **National Association of Trailer Manufacturers (NATM)**. Every trailer that Exiss builds meets or exceeds the requirements set forth by the NATM.



more than a decade. With Exiss' sturdy all-
ilt top-of-the-line aluminum livestock trailers
uild trailers to live up to the rugged demands

ENGINEERED EXCELLENCE

Features like a large 54" side access door, full-length running boards, extruded fenders and EZ Lube axles are examples of how an Exiss trailer is engineered to make your life easier.



INTERIOR DURABILITY

We use 1 5/8" x 3" side posts, 2" x 4" I-Beams, sturdy sidewall extrusion and an interlocking extruded aluminum floor so that your trailer will hold up to the heaviest of loads.



EXTERIOR STRENGTH

Our 6" rear post, heavy-duty cam locks, stout rear gates, five rear hinges and lower gussets make sure that our products will continue to deliver for the long haul.



EXPRESS LIVESTOCK MODELS

The Express STK models are affordable 6'8" wide gooseneck and bumper pull trailers suited for hauling any type of livestock to and from your farm or ranch. The trailer is perfect for smaller operations or a second run-around trailer for larger producers.

MODEL	SIZE	GVWR	EMPTY	AXLE
STK 613 BP	6'8" x 13'	7,000	2,100/2,200	(2) 3,500
STK 616 BP	6'8" x 16'	10,400	2,400/2,700	(2) 5,200
STK 6816 GN	6'8" x 16'	10,400	3,200/3,300	(2) 5,200
STK 6820 GN	6'8" x 20'	12,000	3,500/3,600	(2) 6,000
STK 6824 GN	6'8" x 24'	14,000	3,800/3,900	(2) 7,000



STANDARD SPECIFICATIONS

- All-aluminum construction
- 6'8" or 7'2" inside height
- Interlocking extruded aluminum non-skid plank floor system with 2" x 4" I-beams on 12" centers
- Five 16" 8 hole steel modular wheels with 10 ply radial tires (GN)
- Five 15" 6 hole steel modular wheels with 8 ply radial tires (BP)
- Single leg landing gear with removable handle
- .040 white pre-painted, aluminum exterior finish
- Full length slat with two top air spaces with Plexiglas tracks in stock area
- Heavy-duty 32" streetside access door on gooseneck models; 32" door on bumper pull models
- Full swing center gate w/ slider and heavy-duty slam latch
- Full swing rear door with slider and slider brackets
- One LED dome light with switch on rear frame

POPULAR OPTIONS

- Rubber mat in stock area
- Plexiglas inserts
- Black or silver exterior skin
- Rear gate slam latch
- Many more options available



STK 613 - Compact, great value

EXPRESS STOCK COMBO

Value and versatility meet in the Exiss Express STC stock combo models. You'll enjoy a well-built rugged interior that meets the demands of transporting livestock and horses both in an easy-to-tow 6'8" width when you own an Express STC model. These trailers include a full swing center gate with heavy-duty slam latch and a 4' straight wall tack room.



STC 6820 - Shown with optional equipment



STC 616 - Rugged multi-use trailer

MODEL	SIZE	GVWR	EMPTY	AXLE
STC 616 BP	6'8" x 16'	10,400	2,500/2,800	(2) 5,200
STC 6816 GN	6'8" x 16'	10,400	3,600/3,700	(2) 5,200
STC 6820 GN	6'8" x 20'	12,000	3,900/4,000	(2) 6,000
STC 6824 GN	6'8" x 24'	14,000	4,200/4,300	(2) 7,000

STANDARD SPECIFICATIONS

- All-aluminum construction
- 6'8" or 7'2" inside height
- Interlocking extruded aluminum non-skid plank floor system with 2" x 4" I-beams on 12" centers
- Five 16" 8 hole aluminum wheels with 10 ply radial tires (GN)
- Five 15" 6 hole aluminum wheels with 8 ply radial tires (BP)
- Single leg landing gear with removable handle
- .040 white pre-painted, aluminum exterior finish on nose and sides
- Extruded aluminum slat with two top air spaces with Plexiglas tracks in stock area
- Heavy-duty 32" streetside access door on gooseneck models; 32" door on bumper pull models
- 4' tack room with camper door w/ sliding window, deadbolt and screen door

- Full swing center gate with heavy duty slam latch
- Full swing rear door with slider and slider brackets
- One LED dome light with switch on rear frame; 1-2 lights in tack area

POPULAR OPTIONS

- Halter hooks, blanket bar & brush tray
- Saddle rack
- Carpet on gooseneck floor & drop wall
- Stainless nose
- Rubber floor mats
- Windows in the gooseneck nose
- Plexiglas inserts
- Inside and outside tie rings

STK LIVESTOCK MODELS

Exiss STK models are extremely versatile, rough and rugged options for hauling cattle around your land, to market or anywhere in between. Available in multiple heights and lengths, these quality-built gooseneck and bumper pull models come with today's most popular standard features, and they have an incredible array of options available to make your trailer fit your needs perfectly.



STK 7020 - Shown with optional equipment



STK 716 - Rugged multi-use trailer

MODEL	SIZE	GVWR	EMPTY	AXLE
STK 713 BP	7' x 13'	7,000	2,600/2,700	(2) 3,500
STK 716 BP	7' x 16'	10,400	2,900/3,000	(2) 5,200
STK 7016 GN	7' x 16'	14,000	3,700/3,800	(2) 7,000
STK 7018 GN	7' x 18'	14,000	3,800/3,900	(2) 7,000
STK 7020 GN	7' x 20'	14,000	3,900/4,100	(2) 7,000
STK 7022 GN	7' x 22'	14,000	4,100/4,300	(2) 7,000
STK 7024 GN	7' x 24'	14,000	4,300/4,500	(2) 7,000
STK 7026 GN	7' x 26'	14,000	4,500/4,700	(2) 7,000
STK 7028 GN	7' x 28'	16,000	4,700/4,900	(2) 8,000
STK 7030 GN	7' x 30'	16,000	4,900/5,100	(2) 8,000
STK 8020 GN	8' x 20'	14,000	4,400/4,600	(2) 7,000
STK 8024 GN	8' x 24'	14,000	4,600/4,800	(2) 7,000
STK 8028 GN	8' x 28'	16,000	4,800/5,000	(2) 8,000

STANDARD SPECIFICATIONS

- All-aluminum construction
- 6'8" or 7'2" inside height
- Interlocking extruded aluminum non-skid plank floor system with 2" x 4" I-beams on 10" centers
- Five 16" 8 hole steel modular wheels with 10 ply radial tires; 14 ply on 28' and above (GN)
- Five 15" 6 hole steel wheels with 8 ply tires (713); Five 16" 6 hole steel wheels w/ 10 ply tires (716)
- Single leg landing gear with removable handle
- .063 white pre-painted, aluminum exterior finish
- Running boards with extruded aluminum fenders on 7' models
- Full length slat with two top air spaces with Plexiglas tracks in stock area
- Heavy-duty 54" streetside access door on goosenecks; 37" door on bumper pulls
- Full swing center gate w/ slider and heavy-duty slam latch (2 gates on 24' & above models)
- Full swing rear door with slider and slider brackets
- LED dome lights

POPULAR OPTIONS

- Rubber mat in stock area
- Plexiglas inserts
- Black or silver exterior skin
- Rear gate slam latch
- Adjustable air vent in gooseneck drop
- Many more options available



Patented slam latch w/ outside release



8' long tapered nose w/ heavy-duty kingpin

STC STOCK COMBO MODELS

THE DEFINITION OF VERSATILITY

The Exiss stock combo (STC) models are a great solution for livestock and horse owners who need a versatile trailer with additional storage and functionality. With a spacious tack room to store your necessary equipment, as well as an optional saddle rack and tack equipment, they combine the rough and rugged aspects of an Exiss livestock trailer with the convenient features of an Exiss horse trailer.

MODEL	SIZE	GVWR	EMPTY	AXLE
STC 716 BP	7' x 16'	10,400	3,100/3,200	(2) 5,200
STC 7016 GN	7' x 16'	14,000	4,100/4,200	(2) 7,000
STC 7018 GN	7' x 18'	14,000	4,200/4,300	(2) 7,000
STC 7020 GN	7' x 20'	14,000	4,300/4,500	(2) 7,000
STC 7022 GN	7' x 22'	14,000	4,500/4,700	(2) 7,000
STC 7024 GN	7' x 24'	14,000	4,700/4,900	(2) 7,000
STC 7026 GN	7' x 26'	14,000	4,900/5,100	(2) 7,000
STC 7028 GN	7' x 28'	16,000	5,100/5,300	(2) 8,000
STC 7030 GN	7' x 30'	16,000	5,300/5,500	(2) 8,000
STC 8020 GN	8' x 20'	14,000	4,800/5,000	(2) 7,000
STC 8024 GN	8' x 24'	14,000	5,000/5,200	(2) 7,000
STC 8028 GN	8' x 28'	16,000	5,200/5,400	(2) 8,000

STANDARD SPECIFICATIONS

- All-aluminum construction
- 6'8" or 7'2" inside height
- Interlocking extruded aluminum non-skid plank floor system with 2" x 4" I-beams on 10" centers
- Five 16" 8 hole aluminum wheels with 10 ply radial tires; 14 ply Goodyear tires on 28' and above (GN)
- Five 16" 6 hole aluminum wheels w/ 10 ply tires (BP)
- Single leg landing gear with removable handle
- .063 white pre-painted aluminum exterior finish
- 4' tack room with camper door with window, deadbolt & screen door
- Running boards with extruded aluminum fenders on 7' models
- Full length slat with two top air spaces with Plexiglas tracks
- Streetside access door
- Full swing center gate with heavy-duty slam latch (GN)
- Full swing rear door with slider and heavy-duty slider brackets
- One LED dome light per stall area with switch on rear frame
- Two LED interior lights in tack area with wall switch

POPULAR OPTIONS

- Halter hooks, blanket bar & brush tray
- Saddle rack
- Carpet on gooseneck floor & drop wall
- Stainless nose
- Rubber floor mats
- Windows in the gooseneck nose
- Plexiglas inserts
- Inside and outside tie rings

STC 7024 - Shown with optional equipment



CUSTOM MODELS

CUSTOM-BUILT TO YOUR EXACT SPECIFICATIONS

With years of custom experience and a full staff of design engineers, we will be glad to develop, design and build virtually any trailer you can imagine.



CUSTOM MODEL
40' Triple Axle
Livestock Trailer

POPULAR CUSTOM OPTIONS

- Additional length - up to 44'
- Additional height - up to 8'8"
- Side load ramps
- Additional / upgraded axles
- Air Ride suspension
- Floating gate
- Tie rails
- Many additional items available...

Visit www.exiss.com or call us at **1.877.553.9477** for more information on custom Exiss livestock trailers.

Also Available From Exiss...

Exiss also produces a full line of quality low profile livestock and horse trailers, including the following...



EXISS EXHIBITOR
Low profile bumper pull or gooseneck



EXHIBITOR MINI COMBO
15' bumper pull



EXHIBITOR MINI
11' or 15' bumper pull



Exiss trailers come standard with a fully transferrable, 3-year limited, 8-year structural warranty.